


Technical data sheet: Mat 100W/m² ADPSZV

- CHARACTERISTICS:

- Fiber glass mesh
- Surface output: 100W/m²
- C-C spacing : 8 cm
- Width : 25 / 50 cm
- Cold lead : 2,5 m



Width 25 cm

CODE	Output 230V	Mat length (m)	Surface (m ²)
	100 W/m ²		
64 772 21	120 W	4,75	1,19
64 772 25	160 W	6,65	1,66
64 772 29	210 W	7,90	1,98
64 772 33	270 W	10,70	2,68
64 772 37	330 W	12,55	3,14
64 772 41	390 W	14,75	3,69

Width 50 cm

CODE	Output 230V	Mat length (m)	Surface (m ²)
	100 W/m ²		
64 782 53	540 W	10,85	5,43
64 782 61	680 W	13,40	6,70
64 782 69	820 W	15,60	7,80
64 782 73	980 W	19,95	9,98
64 782 77	1150 W	23,00	11,50
64 782 81	1430 W	28,75	14,38

- **RECOMENDED** for direct underfloor heating

- **HOMOLOGATION:** IEC 60800 – EVPU nº 00101/2012/C

- CONSTRUCTION:

- 1 Cable core : Metallic solid resistance wire (Double core)
- 2 First insulation –Fluoropolymer – 0,15 mm thickness
- 3 Second insulation – Cross linked polyethylene (XLPE) – 0,25 minimum thickness
- 4 Protection screen – Iron and copper wires in helicoidal screen
- 5 Jacket : PVC therm resistant 105°C -0,8 mm thickness

