


Technical data sheet: Mat 120W/m² ADPSZV

- CHARACTERISTICS:

- Fiber glass mesh
- Surface output: 120W/m²
- C-C spacing : 8 cm
- Width : 25 / 50 cm
- Cold lead : 2,5 m



Width 25 cm

CODE	Output 230V	Mat length (m)	Surface (m ²)
	120 W/m ²		
64 773 21	130 W	4,35	1,09
64 773 25	180 W	5,95	1,49
64 773 29	220 W	7,55	1,89
64 773 33	290 W	9,90	2,48
64 773 37	350 W	11,85	2,96
64 773 41	420 W	13,75	3,44

Width 50 cm

CODE	Output 230V	Mat Length (m)	Surface (m ²)
	120 W/m ²		
64 783 49	520 W	8,70	4,35
64 783 53	600 W	9,75	4,88
64 783 61	740 W	12,30	6,15
64 783 69	880 W	14,50	7,25
64 783 73	1070 W	18,30	9,15
64 783 77	1260 W	21,05	10,53
64 783 81	1570 W	26,15	13,08

- **RECOMENDED** for direct underfloor heating

- **HOMOLOGATION:** IEC 60800 – EVPU nº 00101/2012/C

- CONSTRUCTION:

- 1 Cable core : Metallic solid resistance wire (Double core)
- 2 First insulation –Fluoropolymer – 0,15 mm thickness
- 3 Second insulation – Cross linked polyethylene (XLPE) – 0,25 minimum thickness
- 4 Protection screen – Iron and copper wires in helicoidal screen
- 5 Jacket : PVC therm resistant 105°C -0,8 mm thickness

