


## Technical data sheet: Mat 180W/m<sup>2</sup> ADPSZV

### - CHARACTERISTICS:

- Fiber glass mesh
- Surface output: 180W/m<sup>2</sup>
- C-C spacing : 8 cm
- Width : 25 cm
- Cold lead : 2,5 m



CODE	Output 230V	Mat Length (m)	Surface (m <sup>2</sup> )
	180 W/m <sup>2</sup>		
64 775 21	160 W	3,60	0,90
64 775 25	220 W	4,85	1,21
64 775 29	280 W	5,95	1,49
64 775 33	360 W	7,95	1,99
64 775 37	440 W	9,45	2,36
64 775 41	520 W	11,10	2,78
64 775 49	610 W	13,70	3,43
64 775 53	690 W	15,50	3,88

- **RECOMENDED** for tempered floor in bathrooms

- **HOMOLOGATION:** IEC 60800 – EVPU nº 00101/2012/C

### - CONSTRUCTION:

- 1 Cable core : Metallic solid resistance wire (Double core)
- 2 First insulation –Fluoropolymer – 0,15 mm thickness
- 3 Second insulation – Cross linked polyethylene (XLPE) – 0,25 minimum thickness
- 4 Protection screen – Iron and copper wires in helicoidal screen
- 5 Jacket : PVC therm resistant 105°C -0,8 mm thickness

