

Technical data sheet: Mat 60W/m² ADPSZV

CHARACTERISTICS:

- Fiber glass mesh
- Surface output: 60 W/m²
- C-C spacing : 18 cm
- Width : 70 cm
- Cold lead : 2,5 m



CODE	Output 230V	Mat length (m)	Surface (m ²)
	60 W/m ²		
6495517	115 W	2,60	1,82
6495521	140 W	3,26	2,28
6495525	195 W	4,45	3,12
6495529	240 W	5,60	3,92
6495533	320 W	7,25	5,08
6495537	385 W	8,70	6,09
6495541	450 W	10,30	7,21
6495549	540 W	12,40	8,68
6495553	610 W	14,10	9,87
6495557	690 W	15,90	11,13
6495561	770 W	17,40	12,18
6495569	910 W	20,70	14,49
6495573	1120 W	25,60	17,92
6495577	1310 W	29,70	20,79
6495581	1630 W	37,00	25,90
6495585	1970 W	45,00	31,50

- RECOMENDED for underfloor heating in low energy house

- HOMOLOGATION: IEC 60800 – EVPU nº 00101/2012/C

CONSTRUCTION:

- 1 Cable core : Metallic solid resistance wire (Double core)
- 2 First insulation –Fluoropolymer – 0,15 mm thickness
- 3 Second insulation – Cross linked polyethylene (XLPE) – 0,25 minimum thickness
- 4 Protection screen – Iron and copper wires in helicoidal screen
- 5 Jacket : PVC therm resistant 105°C -0,8 mm thickness

