

Installation and user's guide


Radiant panels K+
100, 200, 270, 330, 400W



Important Warnings

- **WARNING: In order to avoid overheating, do not cover the heater.**
- Installation, electrical connection and the first commissioning is permitted to be performed by a worker with relevant qualifications.
- The temperature of environment (surrounding air) where the radiant panel is situated must not exceed 40°C!
- The power supply must be fitted with a network disconnecting device with the minimum distance of disconnected contacts 3.5 mm on all poles. Always use a residual current device with the release current $I_{\Delta n}=30\text{mA}$.
- Damaged lead-in cable of the appliance shall only be replaced by manufacturer or service technician.
- The product type number means the input of the product (330K+ = 330W).
- We recommend to use gloves when manipulating with the panel to prevent any pollution of the radiant front surface of the panel.
- Clean the panel with water and detergent, using a fine brush.
- The panel should not be arranged right under a fixed connection socket.
- This heater isn't fitted with a room temperature control device. Do not use this heater in small rooms if they are occupied by people who cannot be left in the room by themselves unless permanent supervision is provided.
- This appliance can be used by children from the age of 8 and older, and persons with lower physical, sensory or mental abilities or a lack of experience or knowledge providing they are under supervision or have been trained in the use of the appliance in a safe manner and understand the possible danger. Children may not play with the appliance. Cleaning and maintenance by the user must not be carried out by children without supervision.
- Children under 3 years of age should be prevented from accessing the appliance, unless they are constantly supervised. Children from 3 to 8 years of age may switch the appliance on/off only if it is placed or installed in its intended standard operating position and if they are under supervision or have been instructed in the safe use of the appliance and if they understand the possible danger. Children from 3 to 8 years of age mustn't insert the plug into the socket, control or clean the appliance or carry out maintenance that is to be done by the user.

WARNING - Some parts of this product may become very hot and cause burns. Special attention must be paid to this fact in the presence of children and handicapped persons.



1. Use

- empering of church pews, office desks, shop boxes.
- The panels can be installed on flammable materials.

2. Wiring

- Power supply: 230V/50Hz
- Protection class I
- IP 44
- The panel is fitted with a thermal fuse.

3. Installing


- The panels are intended for vertical installation. In case of horizontal installation on the ceiling of a room, hang the panel on a mounting frame (not included in the package), or using chains or cords.
- The minimum distance of the panel front wall and lateral walls from inflammable objects is 10 cm.

Procedure – Vertical mounting:

- Mark the holes according to the table, drill out the holes, insert the dowels and drive the screw into protrude approx. 5 mm.
- Always fix the panel on two upper locks, two lower locks serve to a reverse suspension of the panel.
- Connect the lead-in cable to a fixed power distribution in accordance with the colour marking of wires.
- Put the panel on the two upper locks.


Procedure – Horizontal mounting:

- Position the mounting frame in the location where the panel is to be placed, using a pen, mark holes according to the holes on the frame.
- Drill the holes, insert the wall anchors and attach the mounting frame with the screws.
- Connect the lead-in cable to the mains in accordance with the color of the conductors.
- Slide the panel into the mounting frame.



Panel	X (mm)	Y (mm)	A (mm)	B (mm)	Thickness
100 K+	500	320	305	190	30
200 K+	750		555		
270 K+	1000		805		
330 K+	1250		1055		
400 K+	1500		1305		

Fixing frame



Panel	A (mm)	B (mm)
100 K+	305	110
200 K+	555	
270 K+	805	
330 K+	1055	
400 K+	1305	

4. CE-Declaration of conformity

The product has been designed in conformity with the following standards or other normative documents: EN 60335-1, EN 60335-2-30, EN 60529, EN 62233, EN 62262, EN 55014-1, EN 55014-2, EN 61000-3-2, EN 61000-3-3, 2006/95/EC/LVD, 2004/108/EC/ EMC.

5. Warranty

This product is covered with a 2 years warranty since the date of purchase which applies to defects of material and processing. The complete wording of the Warranty Guidelines is available at the supplier's office or at the websites www.fenixgroup.eu. The warranty does not apply to defects caused by unprofessional intervention, negligence, incorrect use, transport and/or inconvenient storage of the panel. The manufacturer is not responsible for any indirect damage caused by the use of this panel.

Product type:

Date:

Stamp, signature:

Serial number (label on the panel rear side): _ _ _ - _ _ _ - _ _ _ - _ _ _ - _ _ _



CEILHIT SLU

CEILHIT, S.L.U., B-08396079, Carrer de Galileu, 38 - 40
 (08850 Camí Real, GAVÀ - BARCELONA - SPAIN)
 Tel.: (00 34) 93 261 11 25, Fax: (00 34) 93 338 85 99
 e-mail: comercial@ceilhit.es, <http://www.ceilhit.es>